

Alterra 450 4x4

BUILT FOR OUTSIDE. BUILT TO OUT RIDE.

We took the brand- new body style and endless capabilities of the full-sized Alterra, and adapted them for the more compact 450/400 mid-sized models. Part workhorse, part warrior, these machines are more nimble, lightweight and versatile than the competition. Everything from the Duramatic automatic transmission, trail- tuned independent suspension, on- the- fly 2WD/4WD and rear hitch, all the way down to the front winch and powder coated steel rims that give you 10"/25,4 cm of ground clearance. Needless to say, we didn't mess around with these newly styled Alterras.



Red

Green

TECH SPECS

ENGINE

Bore & Stroke (mm)	89 x 71,2
Engine Type	SOHC, 4- stroke, 4- valve EFI
Engine displacement (cc)	443
Gas / Diesel	Gas
Cooling System	Liquid with fan

DIMENSIONS

Overall length (cm/ in.)	214,1
Overall width (cm/ in.)	114,3
Overall height (cm/ in.)	118,9
Wheelbase (cm/ in.)	121,9
Wheelbase (Short/ Long)	Short Wheel Base
Ground Clearance (cm/ in.)	25,4 / 10
Dry weight	305 / 672,4

POWERTRAIN

Transmission	Automatic CVT with EBS
Gear Selection	L / H / N / R
Drive System	2/4 WD Electric
Front brakes	Hydraulic Disc
Rear brakes	Hydraulic Disc

SUSPENSION

Front Suspension	Double A- Arm
Suspension Travel - Front (cm/ in.)	17,8 / 7
Rear Suspension	Double A- Arm
Suspension Travel - Rear (cm/ in.)	17,8 / 7

TYPE APPROVAL

Type Approvals	LOF / Off Road (NH) / T3
Number of Seats	2

TOWING / HAULING

Rack Capacity - Front (kg/ lbs.)	34 / 75
Rack/ Box Capacity - Rear (kg/ lbs.)	68,1 / 150

ADDITIONAL SPECS

Alternator Capacity (amps)	23
Fuel Capacity (lt./ gal.)	15 / 3,96
Speedometer	Digital
Odometer	Digital
Tire Front	25x8-12
Tire Rear	25x10-12
Features	front mounted 3.000 lbs. / 1.360 kg winch fully independent suspension Duramatic automatic transmission Electronic fuel injection (EFI) Powder- coated steel rims Impact resistant racks front and rear Hitch w. 50mm ball and trailer connector (7pin)